

TORO**Workman® GTX**

SIMPLY SUPERIOR

The Workman GTX is a grounds and turf crossover vehicle that boasts an unequalled combination of comfort, utility and control, making it simply superior to the competition. Its increased power, improved steering and exclusive suspension and braking systems make the Workman GTX the most versatile, practical and comfortable utility vehicle in its class. Available in petrol or electric, the Workman GTX features multiple configuration options; including front and rear attachments, a flat bed and a four-seat option. So whether you are setting cups, checking on irrigation, working around campus, or moving people or materials, the Workman GTX has the power and versatility to get the job done right.

toro.com/gtx



FEATURES

Power

Whether you choose the 429 cc petrol or 48 volt A/C electric Workman GTX, power and performance come standard. An improved power to weight ratio boosts payload capacity and productivity by allowing you to do more, everyday!

Steering

An automotive-grade rack and pinion steering system provides more control and lowers steering effort, while operating loaded or empty. This allows operators to focus on the task at hand and nothing else.

Suspension

Coil-over shocks all around the vehicle deliver greater suspension travel and adjustability resulting in a smoother ride and minimised operator fatigue.

Versatility

The Workman GTX is adaptable for any task. Two or four-seat configurations come with bench or bucket seats. Front and rear attachment points for garbage cans, hose reels or walk spreaders free up the bed for more hauling capacity. 4 and 6-foot flat beds are also available.

Hydraulic Disk Brakes

Minimal maintenance, no cable adjustment and less pedal force than mechanical / cable brakes affords the Workman GTX reliable and consistent stopping power.

Durability

Virtually unbreakable exterior components and a powder coated frame and underbody give the Workman GTX superior durability. Run it hard, day after day.

WORKMAN GTX

	PETROL - MODEL 07130TC	ELECTRIC - MODEL 07131TC
POWER SYSTEM	429 cc, air-cooled, single-cylinder Kohler® petrol engine. Meets current EPA & CARB exhaust and evaporative emissions regulations.	48V brushless AC induction drive
STEERING	Manual rack and pinion steering system with ergonomically positioned column. Steering wheel has 2.75 turns lock-to-lock with 13.75" (35 cm) diameter.	
TURNING RADIUS	Turning clearance circle: 20.7', (6.3 m) Inside turning radius: 60.25" (153 cm)	
BRAKES	Front and rear wheel hydraulic disc brakes	
SUSPENSION	FRONT - Modified MacPherson Strut. REAR - Articulating Swing Arm. Adjustable Coil Over Shocks at all four wheels.	
SUSPENSION TRAVEL	Front Suspension Travel: 3.5", Rear Suspension Travel: 4"	
FUEL CAPACITY	5 gallons (18.9 litres)	N/A
GROUND SPEED	16 mph (25.6 km/h) governed	
TRANSAXLE	N/A	17:1 double-reduction high torque
GROUND CLEARANCE	Front: 8.5" (21.6 cm), Rear: 6.1" (15.5 cm)	
TYRES	20 x 8-10, 4-ply	
BATTERIES	One 12-volt starter battery	Eight Trojan® Advanced Deep Cycle 6V batteries featuring a single port fill system and water level indicators.
CONTROLLER	N/A	540 amps max with regenerative motor braking, roll-away protection, thermal cutback, sealed/waterproof, status light and three power modes.
CHARGER	N/A	On-board high efficiency 1kW smart charger with 85-265VAC global input, temperature controlled, sealed & waterproof, remote indicator viewable at charge port.
ELECTRIC MOTOR	N/A	Brushless high-torque AC Induction motor with 5.0kW continuous power.
INSTRUMENTS/DASH	Hour meter, fuel gage, USB power port, headlight switch, on/off ignition key switch, gear selector and parking brake lever. Two cup holders, radio holder and three in-dash storage compartments.	Hour meter, battery level indicator, USB power port, headlight switch, on/off ignition key switch, gear selector and parking brake lever. Two cup holders, radio holder and three in-dash storage compartments.
STARTING	Pedal or key start capability standard	

	Vehicle Configuration	Width	Length	Height	Wheel Base
DIMENSIONS	2-Seat with Bed	47" (1.2 m)	119" (3 m)	50.2" (1.3 m)	86.6" (2.2 m)
	4-Seat with Bed	47" (1.2 m)	144" (3.6 m)	50.2" (1.3 m)	114" (2.9 m)
	2-Seat with 6' Flat Bed	47" (1.2 m)	156" (3.9 m)	50.2" (1.3 m)	114" (2.9 m)

	Vehicle Configuration	Weight	Vehicle Configuration	Weight
WEIGHT	2-Seat with Bed	875 lbs. (397 kg)	2-Seat with Bed	1395 lbs. (633 kg)
	4-Seat with Bed	1150 lbs. (522 kg)	4-Seat with Bed	1670 lbs. (757 kg)
	2-Seat with 6' Flat Bed	1264 lbs. (573 kg)	2-Seat with 6' Flat Bed	1784 lbs. (809 kg)

	Width	Length	Height	Capacity
CARGO BED	38.5" (97.8 cm)	40" (101.6 cm)	11" (27.9 cm)	800 lbs. (363 kg)

VEHICLE CAPACITY	2-seat with bed: 1200 lbs. (544 kg)
------------------	-------------------------------------

TOWING CAPACITY	1000 lbs. (454 kg) Class 1 - 32mm receiver standard.
-----------------	--

OPTIONAL ACCESSORIES	Canopy, solid folding windshield, 4-seat configuration, flat bed, 6-foot flat bed, bench seat, storage box, ball picker mounting bracket, hose reel mounting bracket, walk spreader carrier, trash can mount, bed racking, electric bed lift, brush guard, 12V outlet, Brake/tail/signal lights, ROPS certified hard cab, horn kit, back up alarm kit, parking brake alarm kit, L-track attachment system and all-terrain tyre kit.
----------------------	---

WARRANTY	Two-year or 1500 hour limited warranty. Three-year engine warranty. Refer to the Operator's manual for further details.
----------	---

toro.com.au
Toro Customer Service
1800 356 372

Printed in Australia.
 ©2016 The Toro Company.
 All Rights Reserved.
 200-6488AU



/toroaus

/@toroaus

/toroaustralia



Count on it.